SURFACING RANGE

TR BULL FLOATS

Hand surfacing



ENAR's range of hand tools provides everything you need for the correct preparation and finishing of concrete.

The bull floats are designed for use after vibrating screeds to achieve a finish free of markings and cavities while also reducing flaws. Bull floats are also used on pavements where the concrete does not need to be vibrated and other floors that demand a smooth, imperfect-free surface.

ENAR'S Bull Floats come in lengths of 0.9, 1.2, and 1.8 meters, with a fixed and oscillating handle that can be used in both directions. The new aluminum handle is interchangeable with both models, and they can be linked together to create a larger handle lengths.

- Brush Kit available, that can be installed on both fixed and oscillating bull floats. Allows smoothing and brushing to obtain the desired finish. 900, 1200 and 1800mm brushes available.
- Suitcase Kit available, that includes 1 magnesium profile, 1 oscillating group, 3/4 aluminium handles (45mm diameter, 180cm length) and a robust transport case (360x400x100mm)

 Different float sizes can be offered: 90, 120 and 180cm.









Oscillating Bull Floats

MODEL	Weight (kg)	Profile width (mm)	Length (m)
TRO 900 MG	4.6	205	0.9
TRO 1200 MG	5.8	205	1.2
TRO 1800 MG	7	205	1.8

Fixed Bull Floats

MODEL	Weight (kg)	Profile width (mm)	Length (m)
TR 900 MG	4.4	205	0.9
TR 1200 MG	5.6	205	1.2
TR 1800 MG	6.8	205	1.8